

HM-A200U

Portable Thermal Receipt Printer



Characteristic

- Lightweight design
- Solid & reliable, can withstand multiple 1.8 meter drop impacts
- Dual-mode bluetooth, supports iOS/Android devices connecting
- Supports HereLabel APP editing & printing



Lightweight Design



Small Size & Large Volume



Supports HereLabel
APP Printing



Compatible with
Multi-size Accessories

Specification

Model		HM-A200U
Printing Parameters	Printing Method	Direct Thermal
	Resolution	203 dpi (8 dots/mm)
	Printing Width	Maximum 48 mm
	Printing Speed	Maximum 80 mm/s
	Programming Language	ESC/POS
Printing Media	Media Type	Thermal Receipt Paper
	Media Width	58mm
	Paper Load	Front Paper Loading
Communication Interface	Standard	USB Type-C, Bluetooth 4.0/LE
	Optional	None
Sensor	Standard	Paper Out Detection, TPH Overheat Detection, Cover Open Detection, Battery Temperature Detection
	Optional	None
Instruction and Operation	Monitor	96x36dots, LCD Monitor
	Indication	Indication of operating modes, errors, printing and material status
	Audio/Prompts	Buzzers
	Key	1 Function Key, 1 Power Button
Electrical Parameters	Input	Adapter Input AC 100~240V, 50/60Hz
	Output	Adapter Output DC 5V/1A
	Battery Parameters	2000mAh
Reliability	Thermal Printhead	30km
	Drop Height	Withstands multiple 1.8 meter drop impacts
Environmental Parameters	Operation	-5°C - +50°C, 5%-90% R.H, no-condensation
	Storage	-40°C - +60°C, 5%-95% R.H, no-condensation
Physical Parameters	Size (LxWxH)	99.8x88.15x57.53mm
	Weight	197g (Battery included; accessories not included)
Accreditation		CCC, SRRC

Application



Your Future, Printed

Xiamen Hanin Electronic Technology Co., Ltd.

Address: 1-5F, NO.8, Gaoqi South 12th Road, Xiamen, China

Telephone : + 86-(0) 592 - 5885993

E-mail: overseas@hpert.com

Website: www.hpert.com

Brochure Version: 202311



HPRT Official Website