

TP80K-L

Thermal POS Printer



Characteristic

- Ideal and cost-effective option
- Support Wall Mounting
- Support Error Reprint
- Stylish and sleek appearance



Economical & Practical



Error Reprint



Cutter Jam-Free






Wall Mounting

Specification

Items	Parameter	
Printing Parameter	Printing Method	Direct thermal
	Resolution	203 DPI (8dots/mm)
	Printing Width	72mm (default) / 48mm
	Printing Speed	Max. 200mm/s
	Emulation	ESC/POS
Printing Paper	Paper Type	Thermal continuous paper
	Paper Width	80mm/58mm
	Paper Container Volume	Paper roll with Max. Φ 83mm
	Paper Feed Direction	Upward feed direction
Interface	Standard	Type-B USB 2.0, Ethernet, Cash drawer
Buzzer	Type	Internal Buzzer
		External audible & visual alarm (optional)
Sensor	Standard	TPH over-temperature, Paper end, cover open and cutter jam sensors
	Optional	Black mark sensor
Memory	Flash	2MB
Power supply	Input	AC100V-240V 50/60HZ
	Output	DC 24V±5%, 1.5A
Software	Driver	Windows 7/8/10, Windows Server 2008/2012/2016 Linux, javapos, OPOS, macOS
	Utility Tool	Windows 7/8/10, Windows Server 2008/2012/2016
Reliability	TPH Life	100 km
	Cutter Life	1,200,000 times

Application



Xiamen Hanin Electronic Technology Co.,Ltd.

Address: 1-5F, NO.8,Gaoqi South 12th Road,Xiamen,China

Telephone: +86-(0)592-5885993

E-mail: overseas@hpert.com

Website: www.hpert.com

Brochure Version: 202207



HPRT Official Website